

MAX ATF[®]

Royal Purple Max ATF is a synthetic, high performance, automatic transmission fluid. Its high film strength helps to dramatically reduce heat and wear.

Automatic transmissions generate a great deal of heat and depend on the transmission fluid for cooling and protection. More than 90 percent of all automatic transmission failures are caused by overheating. A 20°F reduction in fluid temperature can double the life of the transmission (Source: Perma Industries Inc.). Max ATF significantly reduces heat to extend the life of your transmission.

Max ATF is fully compatible and can be mixed with other automatic transmission fluids; however, for the best results drain or flush the current oil and then fill with Max ATF.

Max ATF is recommended in vehicles requiring any of these automatic transmission fluids:

Allison C-4, TES-295	Mazda ATF-M III, ATF-MV
Audi G-052-162, G-052-990, G-055-025	Mercedes Benz 236.1, 236.2, 236.3, 236.5, 236.6, 236.7, 236.9, 236.10, 236.11
BMW 7045E, LA2634, LT71141	Mitsubishi SP-II, SP-III
Chrysler ATF+, ATF+2, ATF+3, ATF+4	Nissan 402, Matic-D, Matic-J, Matic-K
Chrysler Mopar AS68RC	Shell 3403, LA2634,
Ford FNR5, MERCON [®] , MERCON [®] V	M-1375.4 (ZF 6-Speed AT)
GM DEXRON [®] , DEXRON [®] II, DEXRON [®] IID, DEXRON [®] III, DEXRON [®] -IIIF, DEXRON [®] IIIG, DEXRON [®] -IIIH	Subaru ATF, ATF-HP
Esso LT 71141	Suzuki 3314, 3317
Honda ATF-Z1 (except in CVT's)	Texaco ETL-7045E, ETL-8072B, N402
Hyundai SP-II, SP-III	Toyota T-III, T-IV
JWS 3309, JWS 3314, JWS 3317	Voith 55.6335.XX (G607)
Kia Red-1, SP-II, SP-III	Volvo Pass Car (4-6 Speed AT), 97340 (Construction Equipment), 97341
Idemitsu K17	VW G-052-162, G-052-990, G-055-025
JASO 1-A	ZF TE-ML, 03D, 04D, 05L, 09, 11B, 14A, 16L, 17C, TE-ML 14B
MAN 339F, 339 V1, 339 V2, 339 Z1, 339 Z2	

PLEASE NOTE: Max ATF is NOT recommended for the following applications: Allison TES-389, DEXRON[®] VI, Ford Type F and MERCON[®] SP & LV, Honda DW-1, Hyundai SP-IV and NWS-9638, Kia SP-IV, JWS 3324, MAN 339 Z3, Mercedes Benz 236.8, 236.12, 236.14 & 236.15, Mitsubishi SP-IV and ATF J2, Nissan Matic-S, Saab 93-165-147, Toyota WS (JWS 3324) and ZF TE-ML 14C. **Max ATF is not recommended for use in any CVT or DCT applications.**

Dexron[®] is a registered trademark of General Motors Corporation.

Mercon[®] is a registered trademark of Ford Motor Company.



TYPICAL PROPERTIES*

ASTM TESTS

D-445	Viscosity	
	cSt @ 40°C	38
	cSt @ 100°C	7.5
	SUS @ 100°F	192
	SUS @ 210°F	50
	cP @ -10°C (14°F)	550
D-2983	cP@ -20°C (-4°F)	1,100
	cP@ -30°C (-22°F)	2,520
	cP@ -40°C (-40°F)	7,950
D-2270	Viscosity Index	169
D-92	Flash Point °F	395
	Pour Point °C	-69
D-4052	Density	
	Specific Gravity @ 60°F	0.84
	Pounds / Gallon	7.01

*PROPERTIES ARE TYPICAL AND MAY VARY.

PART NUMBERS

5-Gal. Pail	05320
6x1-Qt. Case	06320
1-Qt. Bottle*	01320

*AVAILABLE IN CASES ONLY

STANDARD PACKAGING:
1-Quart Bottles
5-Gallon Pails

Part numbers listed
on pages 48– 50.